



BMMG824/1900



BMMG824/1850

Miniature Magnetic Mount Antennas

Our BMMG antennas feature 12' RG-174 coaxial cable fully integrated into the antenna. They are compact, easy to install and are available with a variety of connector options. High performance Pro-Flex™ Plus 195 cable available with 2.4 GHz model.

Features

- One piece construction for easy transport and installation
- Black coated whip assembly and machined polymer base provides minimum visibility
- No tuning required

Antenna Electrical Specifications

Model	Frequency Range	Gain
BMMG824/1900ML195*	824-896 MHz/1850-1990 MHz	2 dBi/6 dBi
BMMG24005ML195*	2400-2484 MHz	5 dBi

Mechanical Specifications

Model	Antenna Height	Rod/Coil Type	Cable
BMMG824/1900ML195*	10.5"	Collinear/Open	12' Pro-Flex™ Plus 195
BMMG24005ML195*	9"	Trilinear/Open	Pro-Flex™ Plus 195



Technical Data

Maximum Power: 50 watts
Nominal Impedance: 50 ohms
VSWR: < 1.5:1
Radiator Material: .062" diameter stainless steel, black chrome finish
Base: Machined polymer
Bushing: Black chrome triple-plated brass
Antenna Base: Molded acrylonitrile butadiene styrene
Mounting Base: Black coated stainless steel
Magnet Mounting Force: 5 lbs minimum
Mount Method: Built-in magnetic base

Connector Options (not all connectors available with all models)

FFME = Female FME

MSMA = SMA Male

NCP = Male N

NF = N female

RPC = Rev Pol TNC

BN = BNC

Please specify connector option when ordering.
Add \$2.00 for N connector option.